

IDEAL TO
EXPAND
YOUR WIFI
COVERAGE

SAGEMCOM

F@ST PACK WIFI PLUS


Powerline Communication device
For high performance network and extended WiFi coverage

- PLC data transmission rate : 500Mbps
- WiFi : 300 Mbps
- 2 + 1 Ethernet Ports
- 1x Additional socket with integrated noise filter
- Works with all internet access boxes / gateways*



* Internet gateway with Ethernet port and / or 200-500Mbps HPAV PLC

F@ST PACK WIFI PLUS



APPLICATIONS

- Expansion of broadband Internet network (with Wi-Fi)
- Connection of Smartphone or tablet anywhere in the house
- Streaming / Gaming on Wi-Fi or Ethernet
- IPTV, IP Camera on Wi-Fi or Ethernet
- Sharing files and devices on Wi-Fi or Ethernet

MAINS SPECIFICATIONS

PLC data transmission rate : 500Mbps**

Wi-Fi data transmission rate : 300Mbps **

2+1 Ethernet Ports

1 x Additional socket with integrated noise filter

Quality of service management

128-bit AES Link Encryption with key management

Power management

** Maximum throughput based on theoretical transmission PHY rate

STANDARDS

HomePlug AV

IEEE 1901

IEEE 802.11 b,g,n

Eup regulation 1275/2008 : less than 1 watt in standby mode

Auto MDI / MDI-X

COEXISTENCE & COMPATIBILITY

Coexistence with HomePlug® 1.0 devices (14Mbps) and HomePlug® 1.0 Turbo devices(85Mbps)

Works with HomePlug AV® devices : 200 Mbps

BOX CONTENT

1 x F@ST PLUG 501P

1 x F@ST PLUG 502W

2 x Ethernet cable with RJ45 connectors

1 x Quick Start Guide

POWER AND CONSUMPTION

Power: 100-240V AC 50-60Hz

F@ST PLUG 501P

Maximum consumption : 2,5W

Idle consumption : 0,5W

F@ST PLUG 502W

Maximum consumption : 5,5W

Minimum consumption : 0,2W

HARDWARE

F@ST PLUG 501P

Chipset AR7420

1 x Female Power Socket type E or type F or type G

1 x Male Power Plug type E+F or type G

1 x Encryption Button to join a network (secured key)

1 x Power activity LED

1 x Powerline activity multicolor LED

1 x Ethernet Link Activity LED

1 x Ethernet Port (Auto MDI/MDI-X)

Dimensions (mm) : 113 x 60 x 85

Weight : 194g



F@ST PLUG 502W

Chipset AR7420 + Chipset AR9341

1 x Male Power Plug type E+F or type G

1 x Button ON/OFF switch

1x Encryption Button to join a network (secured key)

1 x WPS Button (Wi-Fi pairing) - Wi-Fi ON/OFF (long press)

1 x Button reset

1 x Power activity LED

1 x Powerline activity multicolor LED

1x Wi-Fi activity LED

2 x Ethernet activity multicolor LED

2 x Ethernet Ports (Auto MDI/MDI-X)

Parameters configuration with embedded HTML server

Dimensions (mm) 107 x 62 x 49

Weight : 183g



TEMPERATURE & ENVIRONNEMENT

Operating Temperature : 0°C to 45°C

Max Relative Humidity (non condensing) : 90%

WiFi range : up to 300m in free fields

CPL range : up to 500m

All rights reserved. The information and specifications included are subject to change without prior notice. Sagemcom Broadband tries to ensure that all information in this document is correct, but does not accept liability for error or omission. Non contractual document. All trademarks are registered by their respective owners. Simplified joint stock company - Capital 35.703.000 Euros - 518 250 360 RCS Nanterre. 10/2013

Sagemcom Broadband SAS

Headquarters : 250, route de l'Empereur

92848 Rueil-Malmaison Cedex - FRANCE

Tel : +33 (0)1 57 61 10 00 - Fax : +33 (0)1 57 61 10 01

www.sagemcom.com

SAGEMCOM